



RockLock Plus II

SPECIFICATIONS

Style Number:	RLP40122
Plank Size:	7.09" x 48.03"
Overall Thickness:	5.0 mm
Product Construction:	4.0 mm SPC + 1.0 mm IXPE Cushion
Wear Layer:	12 mil with Ceramic Bead Enhanced Urethane Coating
Edge:	Four-Sided Color Cut Bevels
Embossing:	Embossed in Register
Installation Method:	I4F 3L TripleLock® and Click4U®
Recycled Content:	None
Certifications:	GREENGUARD Gold®

Classification	(ASTM 3261-17)	Class III, Type B
Chemical Resistance	(ASTM F 925)	Passes
Critical Radiant Flux	(ASTM E 648-06)	Passes
Dimensional Stability	(ASTM F 2199)	Passes
Residual Indentation	(ASTM F 1914)	Passes
Resistance to Heat	(ASTM F 1514)	Passes
Resistance to Light	(ASTM F 1515)	Passes
Smoke Density	(ASTM E 662)	Passes
Thickness	(ASTM F 387)	Passes
Static Load Limit	(ASTM F 970)	Passes
Delta IIC	(ASTM E2197-2003)	Δ25
Impact Insulation	(ASTM E492-09)	IIC 60
Sound Transmission	(ASTM E90-2009)	STC 62

PACKAGING

Square Feet Per Carton:	23.64	Pieces Per Carton:	10
Square Feet Per Pallet:	1,418.4	Cartons Per Pallet:	60
Square Feet Per Container:	25,531.2	Pallets Per Container:	18
Weight Per Carton:	38.93 lbs	Weight Per Pallet:	2,385.8 lbs

COLOR LINE

5041 Lewisburg	5044 Shepherdstown	5061 Tunnelton	5072 Davis	5037 Cass
5042 Snowshoe	5051 Wisp	5062 Rowlesburg	5081 Bowden	5038 Durbin
5043 Roanoke	5052 Timberline	5071 Thomas	5082 Parsons	5039 Beverly

WARRANTIES

Lifetime Limited Waterproof*	Lifetime Limited Residential*	10 Year Limited Commercial*
------------------------------	-------------------------------	-----------------------------

*Please visit our website for full warranty details.