

# Heavyweight Tile

## ☞ SPECIFICATIONS

<b>Style Number:</b>	HW30282
<b>Plank Size:</b>	12" x 24"
<b>Product Construction:</b>	3.0 mm Flexible LVT
<b>Wear Layer:</b>	28 mil with MaxProtect® Coating
<b>Edge:</b>	Square
<b>Gloss Level:</b>	Matte
<b>Installation Method:</b>	Glue Down
<b>Recycled Content:</b>	None
<b>Certifications:</b>	GreenGuard Gold®

<b>Classification</b>	<b>ASTM F1700-20</b>	Class III, Type B
<b>Chemical Resistance</b>	<b>ASTM F 925</b>	Passes
<b>Critical Radiant Flux</b>	<b>ASTM E 648-06</b>	Passes
<b>Dimensional Stability</b>	<b>ASTM F 2199</b>	Passes
<b>Residual Indentation</b>	<b>ASTM F 1914</b>	Passes
<b>Resistance to Heat</b>	<b>ASTM F 1514</b>	Passes
<b>Resistance to Light</b>	<b>ASTM F 1515</b>	Passes
<b>Smoke Density</b>	<b>ASTM E 662</b>	Passes
<b>Thickness, Product</b>	<b>ASTM F 386</b>	Passes
<b>Thickness, Wearlayer</b>	<b>ASTM F410</b>	Passes
<b>Slip Resistance</b>	<b>ANSI A 137</b>	Passes
<b>Flexibility</b>	<b>ASTM F137</b>	Passes
<b>Smoke Density</b>	<b>ASTM E 662</b>	Passes
<b>Slip Resistance</b>	<b>ANSI A 137</b>	Passes
<b>Delta IIC</b>	<b>ASTM E2179-03(2016)</b>	4
<b>Impact Insulation</b>	<b>ASTM E492-09(2016)</b>	43

## ☞ PACKAGING

<b>Square Feet Per Carton:</b>	36	<b>Pieces Per Carton:</b>	18
<b>Square Feet Per Pallet:</b>	1,872	<b>Cartons Per Pallet:</b>	52
<b>Square Feet Per Container:</b>	37,440	<b>Pallets Per Container:</b>	20
<b>Weight Per Carton:</b>	39.237 lbs	<b>Weight Per Pallet:</b>	2,040.32 lbs

## ☞ COLOR LINE

3073 Anacostia	3074 Bellevue
----------------	---------------

## ☞ WARRANTIES

Lifetime Limited Residential Wear*	30 Year Limited Commercial Wear*
------------------------------------	----------------------------------

\*Please visit our website for full warranty details.