



RockLock Plus

SPECIFICATIONS

Style Number:	RLP42121
Nominal Plank Size:	6" x 48"
Overall Thickness:	5.2 mm
Product Construction:	4.2 mm SPC + 1.0 mm IXPE Cushion
Wear Layer:	12 mil with Ceramic Bead Enhanced Urethane Coating
Edge:	Four-Sided Color Cut Bevels
Embossing:	Wood Embossing
Installation Method:	Uniclic® Angle-Tap
Recycled Content:	None
Certifications:	FloorScore®

Classification	(ASTM F1700-04)	Class III, Type B
Chemical Resistance	(ASTM F 925)	Passes
Critical Radiant Flux	(ASTM E 648-06)	Passes
Dimensional Stability	(ASTM F 2199)	Passes
Residual Indentation	(ASTM F 1914)	Passes
Resistance to Heat	(ASTM F 1514)	Passes
Resistance to Light	(ASTM F 1515)	Passes
Smoke Density	(ASTM E 662)	Passes
Thickness	(ASTM F 387)	Passes
Static Load Limit	(ASTM F 970)	Passes
Delta IIC	(ASTM E2197-2003)	Δ25
Impact Insulation	(ASTM E492-09)	IIC 60
Sound Transmission	(ASTM E90-2009)	STC 62

PACKAGING

Square Feet Per Carton:	19.7	Pieces Per Carton:	10
Square Feet Per Pallet:	1,182	Cartons Per Pallet:	60
Square Feet Per Container:	23,640	Pallets Per Container:	20
Weight Per Carton:	34.5 lbs	Weight Per Pallet:	2,070 lbs

COLOR LINE

5231 Acadia	5234 Seneca
5232 Cumberland	5235 Teton
5233 Denali	5236 Yosemite

WARRANTIES

Lifetime Limited Waterproof*	Lifetime Limited Residential*	10 Year Limited Commercial*
------------------------------	-------------------------------	-----------------------------

*Please visit our website for full warranty details.