

RockLock Plus Tile

∂ SPECIFICATIONS

Style Number: Plank Size: Construction: Wear Layer: Edge: Installation Method: Embossing: Recycled Content: Certifications:	RLP40123 12.01" x 24.01" x 5 mm 4 mm SPC + 1 mm IXPE Cushion 12 mil with MaxProtect® Coating Painted Bevels I4F 3L TripleLock® and Click4U® Embossed in Register None GREENGUARD Gold®		
Classification Chemical Resistance Critical Radiant Flux Dimensional Stability Residual Indentation Resistance to Heat Resistance to Light Smoke Density Thickness	(ASTM 3261-17) (ASTM F 925) (ASTM E 648-06) (ASTM F 2199) (ASTM F 1914) (ASTM F 1514) (ASTM F 1515) (ASTM E 662) (ASTM F 387)	Clas Pass Pass Pass Pass Pass Pass Pass P	Ses Ses Ses Ses Ses Ses
Square Feet Per Carton: Square Feet Per Pallet: Square Feet Per Container: Weight Per Carton:	20.03 1,442.16 28,843.20 33.96 lbs	Pieces Per Carton: Cartons Per Pallet: Pallets Per Container: Weight Per Pallet:	10 72 20 2,385.8 lbs
SKUS 5020 Flintstone		5022 La Vale	
5021 Klondike		5028 Frostburg	

*	*	*
l if a time a l imait a al M/ata ma wa af	Lifetime e Linette el De stalentiel	
Lifetime Limited Waterproof	Lifetime Limited Residential	10 Year Limited Commercial

*Please visit our website for full warranty details.