



# RockLock Plus II

## ☞ SPECIFICATIONS

<b>Style Number:</b>	RLP40122
<b>Nominal Plank Size:</b>	7" x 48"
<b>Overall Thickness:</b>	5.0 mm
<b>Product Construction:</b>	4.0 mm SPC + 1.0 mm IXPE Cushion
<b>Wear Layer:</b>	12 mil with Ceramic Bead Enhanced Urethane Coating
<b>Edge:</b>	Four-Sided Color Cut Bevels
<b>Embossing:</b>	Embossed in Register
<b>Installation Method:</b>	I4F 3L TripleLock® and Click4U®
<b>Recycled Content:</b>	None
<b>Certifications:</b>	FloorScore®

<b>Classification</b>	<b>(ASTM 3261-17)</b>	Class III, Type B
<b>Chemical Resistance</b>	<b>(ASTM F 925)</b>	Passes
<b>Critical Radiant Flux</b>	<b>(ASTM E 648-06)</b>	Passes
<b>Dimensional Stability</b>	<b>(ASTM F 2199)</b>	Passes
<b>Residual Indentation</b>	<b>(ASTM F 1914)</b>	Passes
<b>Resistance to Heat</b>	<b>(ASTM F 1514)</b>	Passes
<b>Resistance to Light</b>	<b>(ASTM F 1515)</b>	Passes
<b>Smoke Density</b>	<b>(ASTM E 662)</b>	Passes
<b>Thickness</b>	<b>(ASTM F 387)</b>	Passes
<b>Static Load Limit</b>	<b>(ASTM F 970)</b>	Passes
<b>Delta IIC</b>	<b>(ASTM E2197-2003)</b>	Δ25
<b>Impact Insulation</b>	<b>(ASTM E492-09)</b>	IIC 60
<b>Sound Transmission</b>	<b>(ASTM E90-2009)</b>	STC 62

## ☞ PACKAGING

<b>Square Feet Per Carton:</b>	23.64	<b>Pieces Per Carton:</b>	10
<b>Square Feet Per Pallet:</b>	1,418.4	<b>Cartons Per Pallet:</b>	60
<b>Square Feet Per Container:</b>	25,531.2	<b>Pallets Per Container:</b>	18
<b>Weight Per Carton:</b>	38.93 lbs	<b>Weight Per Pallet:</b>	2,385.8 lbs

## ☞ COLOR LINE

5041 Lewisburg	5044 Shepherdstown	5061 Tunnelton	5072 Davis
5042 Snowshoe	5051 Wisp	5062 Rowlesburg	5081 Bowden
5043 Roanoke	5052 Timberline	5071 Thomas	5082 Parsons

## ☞ WARRANTIES

Lifetime Limited Waterproof*	Lifetime Limited Residential*	10 Year Limited Commercial*
------------------------------	-------------------------------	-----------------------------

\*Please visit our website for full warranty details.