

RockLock Plus Tile

₴ SPECIFICATIONS

Style Number: RLP42202

Plank Size: 12.01" x 24.01" x 5.2 mm

Construction: 5.2 mm SPC + 1 mm MaxPro™

Wear Layer: 20 mil with MaxProtect®

Edge: ColorEdge™

Installation Method: I4F 3L TripleLock® and Click4U®

Embossing: Embossed in Register

Recycled Content: None

Certifications: GREENGUARD Gold®

Classification (ASTM 3261-17) Class III, Type B

Chemical Resistance Passes (ASTM F 925) **Critical Radiant Flux** (ASTM E 648-06) Passes **Dimensional Stability** (ASTM F 2199) Passes **Residual Indentation** Passes (ASTM F 1914) **Resistance to Heat** (ASTM F 1514) Passes **Resistance to Light** (ASTM F 1515) Passes **Smoke Density** (ASTM E 662) Passes **Thickness** (ASTM F 387) **Passes**

PACKAGING

Square Feet Per Carton:20.03Pieces Per Carton:10Square Feet Per Pallet:1,442.16Cartons Per Pallet:72Square Feet Per Container:28,843.20Pallets Per Container:20

Weight Per Carton: 33.96 lbs Weight Per Pallet: 2,385.8 lbs

⋛ SKUS

5020 Flintstone 5022 La Vale 5021 Klondike 5028 Frostburg

WARRANTIES

Lifetime Limited Waterproof Lifetime Limited Residential 10 Year Limited Light Commercial