

# Heavyweight

## ☞ SPECIFICATIONS

<b>Style Number:</b>	HW30281
<b>Plank Size:</b>	7" x 48"
<b>Product Construction:</b>	3.0 mm Glue Down LVT
<b>Wear Layer:</b>	28 mil with MaxProtect® Coating
<b>Edge:</b>	Square
<b>Gloss Level:</b>	Matte
<b>Installation Method:</b>	Glue Down
<b>Recycled Content:</b>	None
<b>Certifications:</b>	FloorScore®

<b>Classification</b>	<b>ASTM F1700-20</b>	Class III, Type B
<b>Chemical Resistance</b>	<b>ASTM F 925</b>	Passes
<b>Critical Radiant Flux</b>	<b>ASTM E 648-06</b>	Class I
<b>Dimensional Stability</b>	<b>ASTM F 2199</b>	Passes
<b>Residual Indentation</b>	<b>ASTM F 1914</b>	Passes
<b>Resistance to Heat</b>	<b>ASTM F 1514</b>	Passes
<b>Resistance to Light</b>	<b>ASTM F 1515</b>	Passes
<b>Smoke Density</b>	<b>ASTM E 662</b>	Passes
<b>Thickness, Product</b>	<b>ASTM F 386</b>	Passes
<b>Thickness, Wearlayer</b>	<b>ASTM F410</b>	Passes
<b>Slip Resistance</b>	<b>ANSI A 137</b>	Passes
<b>Flexibility</b>	<b>ASTM F137</b>	Passes
<b>Delta IIC</b>	<b>ASTM E2179-03(2016)</b>	4
<b>IIC</b>	<b>ASTM E492-09(2016)</b>	43

## ☞ PACKAGING

<b>Square Feet Per Carton:</b>	35	<b>Pieces Per Carton:</b>	15
<b>Square Feet Per Pallet:</b>	1,925	<b>Cartons Per Pallet:</b>	55
<b>Square Feet Per Container:</b>	38,500	<b>Pallets Per Container:</b>	20
<b>Weight Per Carton:</b>	37.803 lbs	<b>Weight Per Pallet:</b>	2,129.4 lbs

## ☞ COLOR LINE

30045 Carytown	30083 Roxborough	30106 Kempsville	30141 Dupont Circle
30053 Hampden	30085 Germantown	30107 Sandbridge	30142 Foggy Bottom
30054 Canton	30091 Carnegie	30108 Lynnhaven	30143 Georgetown
30055 Pimlico	30092 Lawrenceville	30125 Leola	
30056 Woodberry	30095 Shadyside	30126 Manheim	

## ☞ WARRANTIES

Lifetime Limited Residential Wear*	30 Year Limited Commercial Wear*
------------------------------------	----------------------------------

\*Please visit our website for full warranty details.