

## RockLock Plus Tile

## **∂** SPECIFICATIONS

Style Number: Plank Size: Overall Thickness: Construction: Wear Layer: Edge: Installation Method: Embossing: Recycled Content:	EAVROCL 12.01" x 24.01" 6 mm 5 mm Rigidcore + 1 mm Max 20 mil with MaxProtect® ColorEdge® Floating Overall None	StepPro™	
Classification Chemical Resistance Critical Radiant Flux Dimensional Stability Residual Indentation Resistance to Heat Resistance to Light Smoke Density Thickness	(ASTM 3261-17) (ASTM F 925) (ASTM E 648-06) (ASTM F 2199) (ASTM F 1914) (ASTM F 1514) (ASTM F 1515) (ASTM E 662) (ASTM F 387)	Class III, Type B Passes Passes Passes Passes Passes Passes Passes Passes Passes	

Square Feet Per Carton:	18.02	Pieces Per Carton:	9
Square Feet Per Pallet:	1,189.57	Cartons Per Pallet:	66
Square Feet Per Container:	28,543.68	Pallets Per Container:	24
Weight Per Carton:	34.36 lbs	Weight Per Pallet:	2,267.76 lbs

## ê skus

## *e* WARRANTIES

*	*	*
Lifetime Limited Waterproof	Lifetime Limited Residential	10 Year Limited Light Commercial
	Ellotimo Elimito integracia	ro roar Einnoa Eight Commorolar